


# QuikRead go<sup>®</sup>



easy CRP

wrCRP

wrCRP+Hb

CRP

CRP+Hb

HbA1c

Strep A

iFOBT

<b>Sample type</b>	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood, serum, plasma	Whole blood	Throat sample	Faeces
<b>Sampling</b>	Sample collector (10 µl)	Orange striped capillary	Orange striped capillary	Blue striped capillary	Blue striped capillary	Sample collector (1 µl)	Throat swab	Sampling vial
<b>Sample volume</b>	10 µl	10 µl	10 µl	20 µl	20 µl	1 µl	NA	10 mg
<b>Sample stability in test cuvette</b>	2 h	2 h	2 h	2 h	2 h	5 min	4 h	2 h
<b>Measurement results within</b>	2 min	2 min	2 min	2 min	2 min	<6 min	4 min, strong positives 2 min	3 min
<b>Measuring range</b>	1–200 mg/l	0.5–200 mg/l	CRP 0.5–200 mg/l Hb 50–220 g/l	5–200 mg/l	CRP 5–200 mg/l Hb 50–245 g/l	20–140 mmol/mol 4.0–15.0 %	Positive/negative	10–200 µg/g (50–1000 ng/ml)
<b>Unique combination: 1 analysis – 2 results</b>	–	–	yes	–	yes	–	–	–
<b>Number of tests</b>	50	50	50	50	50	25	50	50
<b>Storage</b>	2–25°C	2–25°C	2–25°C	2–25°C 4 weeks 2–8°C	2–25°C 4 weeks 2–8°C	18–25°C 2 months 2–8°C	2–25°C	2–25°C 4 weeks 2–8°C
<b>Software version</b>	7.6.2 or newer	7.5.1 or newer	7.5.1 or newer	All versions	4.1 or newer	8.1.1 or newer	4.1 or newer	6.5.1 or newer
<b>QuikRead go Instrument connectivity to HIS and LIS systems</b>	yes	yes	yes	yes	yes	yes	yes	yes

Email for orders: [orders@aidian.eu](mailto:orders@aidian.eu)

[www.aidian.eu](http://www.aidian.eu) / [www.quikread.com](http://www.quikread.com) / [www.tackleamr.com](http://www.tackleamr.com)

**AIDIAN**

[www.aidian.eu](http://www.aidian.eu)



## QuikRead go Instrument

<b>Method</b>	Immunoturbidimetric and photometric
<b>Dimensions</b>	27 cm (l) x 15.5 cm (w) x 14.5 cm (h)
<b>Weight</b>	1.7 kg without power supply
<b>Storage and transportation</b>	Between 2 °C and 35 °C. Protect from rain and humidity.
<b>Country of origin</b>	Finland
<b>Power requirements</b>	100–240 V AC, 50–60 Hz power supply or accumulator unit. Power consumption 8 W.
<b>Battery use possibility</b>	Yes, supplied separately. Note that only an accumulator unit supplied for QuikRead go can be used.
<b>Memory capacity</b>	100 patient results, 100 QC results and 100 LIS offline results.
<b>Available user interface languages</b>	23
<b>Additional printer available</b>	yes
<b>Barcode reader available</b>	yes

## QuikRead go connectivity specifications

<b>Network TCP/IP communication</b>	RJ45 LAN, optional WLAN USB adapter
<b>Serial communication</b>	Through RJ45 via optional QuikRead go serial cable (RJ45 to RS-232)*
<b>Supported protocols</b>	LIS01-A2 (ASTM), POCT1-A2
<b>Communication type</b>	Unidirectional (LIS01-A2, POCT1-A2), bidirectional (POCT1-A2)
<b>USB ports</b>	3 x Type A USB port 1 x Type B USB port
<b>Sent information</b>	Patient results, QC results, result comments, notifications and error messages
<b>Result sending</b>	Automatic (LIS01-A2, POCT1-A2) or manual (LIS01-A2)
<b>Instrument software remote update</b>	yes**
<b>Remote lock/unlock</b>	yes**
<b>Remote user management</b>	yes**
<b>QC material data</b>	yes**
<b>Patient list import / positive patient identification</b>	yes**
<b>Instrument configuration</b>	yes**
<b>Instrument time setting</b>	yes**

\* LIS01-A2 only, \*\* POCT1-A2 only